



KD Auctions

Multiple Nationwide Facilities Seeking to Liquidate Surplus Machinery!!!!!!

Arizona

United States

Ends from Mar 31, 2026 9am PT (5pm BST)

Lot	Description
0	Buyers located outside the United States, Canada, or Mexico must provide a \$3,000.00 wire transfer deposit to participate in our auctions. Deposits must be confirmed before the auction begins and may take up to 48 hours to process. Deposits will either be applied to the buyer's invoice or refunded w ...[more]
000	Assets in this sale are in various locations. Before bidding, verify the item's location.
00	All Invoices must be paid in full within 24 hours of closing of the sale. No Exceptions. Acceptable forms of payment include wire transfer, ACH, cashier's check, company check with bank letter of guarantee. Once the sale concludes, you'll receive an invoice from no-reply@wavebid.com. In the case of ...[more]
100	2014 Flow Mach 4 4030c, 10.2 x 13.1 DWJ Head CNC Waterjet, Table Width 10.2', Table Length 13.1', Control Flowmaster, Pump 50 HP, Max Cutting Pressure 60,000 PSI, Rapid Traverse 1,400 IPM, Contour Speed 1,000 IPM, Power Requirement 460-480/3/60, 2D Drawing and Cutting, Dynamic Head with Taper Compe ...[more]
102	2022 Jet VBS-3612, Band Saw, Table Size 23-5/8" x 27 1/2", Table Height at 90 Degrees 40", Table Tilt 10 Degree L / 45 Degree R, Height Capacity 12", Throat Capacity 36", Blade Width 1/8 Min / 1 Max, Motor 3 HP, Dimensions 69 x 32 x 81, Approx Shipping Weight 1760 Lbs, Power Requirement 230/460V 3 P ...[more]
103	2022 Artec Eva 3D Scanner S/N EV.30.88662720 Scanning Technology: Structured-Light (White Light) 3D Accuracy: Up to 0.1 mm 3D Resolution: Up to 0.2 mm in HD Mode; Standard resolution up to 0.5 mm Color Capture: Produces vibrant full-color 3D models Calibration: No calibration or markers requir ...[more]
200	2013 Omax MaxiEM 1530, 5.2 x 10.1 CNC Waterjet, Table Width 5.2', Table Length 10.1', Cutting Envelope 5.2' x 10.1', Control IntelliMax, Pump 20 HP, Max Cutting Pressure 50,000 PSI, X-Y Cutting Travel 5.2" x 10", Max Supported Material Load 300 lbs / sq ft., Power Requirement 480/3/60, Operating ...[more]
201	2011 Techni ILS 510, 5 x 10 CNC Waterjet, Table Width 5', Table Length 10', Control Techni, Pump 30 HP, Max Cutting Pressure 60,000 PSI, Accustream Intensifier Pump, Closed Loop System Including Chiller, Open Bed Design, Abrasive Hopper
202	2014 Vicon Elite, 5' x 10' Hypertherm HPR 130XD Plasma Cutter, Table Width 5', Table Length 10', Control Vicon, Power Source Hypertherm HPR 130XD, Arc Glide Torch Height Control, Dual Drive Gantry System, Power Max 65 Power Source, Dust Collector Included
300	Gould & Eberhardt 36HS, Vertical Gear Hobber, Max Workpiece Diameter 36", Max Diametric Pitch 2.5DP, Max Hob Diameter 6", Axial Travel 15", Table Diameter 20", Change Gears, Conventional Control, Single Thread Index, Coolant System, Tailstock
350	2018 QL Servo S3 Barfeeder SN: 18002100100
351	2016 QL Servo S2 Barfeeder SN: 27186901

352	2015 QLS80 S2 (4) Barfeeder SN: 27150001
353	2015 QLS80 S2 (3) Barfeeder SN: 27146901
354	2015 QLS80 S2 (2) Barfeeder SN: 27149101
355	2015 QLS80 S2 (1) Barfeeder SN: 27167301
356	2013 Alpha SL65-S Barfeeder SN: 29027201
357	2012 QLS80 S2 (1) Barfeeder SN: 27047301
358	2012 QLS80 S2 (2) Barfeeder SN: 27048401
400	2000 Missler DEB 340 CE, Automatic Horizontal Bandsaw, Cutting Capacity 13.4" X 13.4" (340 X 340mm), Cutting Speed Range 30 @ 400 Ft/Min, Blade Dimensions 34 X 1.1 X 5000, 1-1/4" X 0.042" X 16'-0.84", Maximum in Automatic Cycle 9999.9mm, 99.999", Number of Programmable Sequences 99, Roller Conveyor
401	1979 Hercules AJAX HR2000, #25 Heavy Duty Gap Bed Engine Lathe, Type #25 Heavy Duty, Spindle Speed (16) 12 to 1200 RPM, Swing Over Ways 27", Distance Between Centers 84", Diameter of Spindle Hole 4", Motor 20 HP, Rapid Travel, Gap Bed, Taper Attachment, Thread Dial, Hardened Ways
402	2010 Flow Mach 3 612, 6 x 12 CNC Waterjet, Table Width 6', Table Length 12', Control Flow PC Based, Pump 50 HP, Max Cutting Pressure 60,000 PSI, Abrasive Hopper, Roll-Around Control, Straight Cutting Head, Flying Bridge Design Easy Access on 3 Sides of the Tank
450	1969 Lodge & Shipley Powerturn, Engine Lathe, Chuck Size 21", Bar Capacity 2.5", Swing 26.5", Distance Between Centers 48", 2 Steady Rests, 4 Jaw Chuck
451	1996 Okuma MX-45VAE, CNC Vertical Machining Center, X-Axis Travel 30", Y-Axis Travel 18.1", Z-Axis Travel 17.7", Spindle Speed 7,000 RPM, Spindle Taper CAT 40, Spindle Motor 10 HP, Tool Magazine Capacity 20 ATC, Control Okuma, Remote Jog Handle, Rigid Tapping
500	2003 Haas VF-4, CNC Vertical Machining Center, X-Axis Travel 50", Y-Axis Travel 20", Z-Axis Travel 25", Spindle Speed 10,000 RPM, Spindle Taper CAT 40, Tool Magazine Capacity 20 ATC, Control Haas CNC, 4th Axis Rotary Table, Chip Auger, Haas HRT-210 4th Axis Rotary Table, 2 Speed Gearbox, Remote Jog ...[more]
501	2005 Haas VF-2D, CNC Vertical Machining Center, X-Axis Travel 30", Y-Axis Travel 16", Z-Axis Travel 20", Spindle Speed 10,000 RPM, Spindle Taper CAT 40, Spindle Motor 20 HP, Tool Magazine Capacity 24 ATC, Control Haas CNC, Chip Auger, Programmable Coolant Nozzle
503	Central Pneumatic Sttel Blast Cabinet, Air Pressure 125 PSI Max, Air Inlet Size 1/4" NPT, Nozzle Sizes 4, 5, 6 and 7 mm, Lamp Power Supply 115VAC, CFM Requirements 12-16 CFM @ 70 - 115 PSI
504	Bridgeport Machines Knee Mill with Z Axis Drilling and Milling. Inc S/N RD662
505	Enco 30 Milling & Drilling Machine Model 105-1110 S/N 948850
508	Craftsman Table Top Lathe

511	Rigid Table Top Belt Sander
514	C.C. Hare's Manual Hand Break
515	1994 Enco Manual Break 130-5605 S/N 940316
516	Duro Metal Products Vertical Bandsaw Co S/N G23 152SI
520	2020 Sany SCP130SH4, Diesel Forklift, Lifting Capacity 28,600 lbs, 10.00-20 16PR Pneumatic STND PLY, 148" MLS and 143" OAL Duplex, Climate Control, Cummins 4.5L Tier 4F, Dana T10 3 Speed Auto Shift Transmission, Kessler D61, LED Amber Strobe / Stop / Tail Lights, Less than 700 Hours, Recent PM Done ...[more]
521	2019 Omax 80X, 6.8' x 13.4' CNC Waterjet, Table Width 6.8', Table Length 13.4', Control Omax Intelli-MAX, Pump 50 HP, Max Cutting Pressure 60,000 PSI, Power Requirement 480/3/60, Approximately 5000 Hours on Pump, Intelli-Trax Drive with Linear Encoder in X-Axis, Preloaded Ball Screw on Y-Axis, 2500 ...[more]
580	1995 Supermax LG-2236 Engine Lathe, Chuck Size 12", Bar Capacity 2.5", Turning Diameter 22", Spindle Speed 1,150 RPM, Distance Between Centers 48", Power Requirement 220V/60/3PH, Quick Change Tool Post, Tailstock, S/N 8306-010
600	1968 Blanchard 32-60, Vertical Rotary Surface Grinder, Chuck Diameter 60", Grinding Wheel Diameter 32", Swing Inside Guards 64", Height Under New Wheel 18", Wheel Speed 500 RPM, Chuck Speeds (6) 5.6- 8.7-12.9- 20.7 RPM, Inf. Variable Power Downfeed 0.004" to .080" IPM, Motor 100 HP, Max Weight of Wo ...[more]
601	2008 Okuma Millac 853PF-5X, CNC Vertical Machining Center, X-Axis Travel 120.8", Y-Axis Travel 33.46", Z-Axis Travel 27.56", Spindle Speed 12,000 RPM, Spindle Taper CAT 50, Spindle Motor 75 HP, Tool Magazine Capacity 30 ATC, Control Fanuc 31i, Chip Conveyor, 5th Axis Ready, A/B-Axis Rotation + 35 De ...[more]
602	2012 Mazak Integrex i-500V, CNC Vertical/Horizontal Multitasking Center, Pallet Size (Millimeters) 610, Pallet Size 24" x 24", X-Axis Travel 43.31", Y-Axis Travel 31.5", Z-Axis Travel 35.43", Tool Magazine Capacity 80 ATC, Spindle Speed 12,000 RPM, Spindle Taper CAT 40, Spindle Motor 30 HP, Control ...[more]
603	OmniTurn GT-75 Seires III
604	Burgmaster Houdaille 6 Station Drill Press S/N 5858
605	Doerr Electric Corp LR24684, 3 Phase, 1/2 HP, 60 HZ, 1725 RPM S/N R60116SH818
606	2023 SCM Nova SI 400 Table Saw, Sliding Carriage Length 10.5', Main Blade Diameter 15.75", Main Blade Arbor 1", Scoring Blade Diameter 4.72", Scoring Blade Arbor 0.75", Main Blade Speed 3000–5000 RPM, Scoring Blade Speed 8500 RPM, Blade Tilt Range -45° to +45°, Max Cutting Height at 90° 5.5", Max Cu ...[more]
1000	More Lots Coming Soon!!